



HEATHKIT STEREO AMPLIFIER MODEL A-A-100

- ENCLOSED NUMBER AND LETTERED DESIGNATIONS APPEAR ON CIRCUIT BOARDS. NUMBERS 20, 21, 22, 25, 43, 44, 44 ARE GROUND CONNECTIONS AND DO NOT APPEAR ON THE SCHEMATIC.
- ALL PAPER CAPACITORS RATED AT 400 VOLTS DC UNLESS SPECIFIED OTHERWISE.
- ALL CAPACITOR VALUES ARE IN μ F UNLESS SPECIFIED OTHERWISE.
- ALL RESISTORS ARE 1/2 WATT UNLESS SPECIFIED OTHERWISE.
- ROTARY SWITCH WAFERS ARE VIEWED FROM FRONT. SWITCHES SHOWN IN MAX. COUNTERCLOCKWISE POSITION.
- INDICATES CLOCKWISE ROTATION.
- INDICATES VOLTAGE READING.
- VOLTAGES TAKEN WITH HEATHKIT VTVM. 117 VOLT LINE SOURCE. VOLTAGES MAY VARY $\pm 20\%$ DUE TO TOLERANCE OF COMPONENTS. VOLTAGES MARKED * SHOULD NOT VARY MORE THAN $\pm 10\%$.
- DC VOLTAGES TAKEN FROM TEST POINT TO CHASSIS GROUND, UNDER NO-SIGNAL CONDITIONS.