Technical Manual

L33 Lancer



N/A

SYSTEM COMPONENTS:

FULL RANGE DRIVER:

LE8

Cone Kit:

C8RLE8T

Nom. Impedance:

8 Ohm

Dynamic Test Input V:

4

Sweep Frequency Hz:

20-1200

D.C. Resistance Ohms:

5.1 minimum

5.9 maximum

Gap Gauge:

.048"

Notes:

Aquaplas On Cone.

Bond 2 foam pads to underside of dome.

Early Models No Aquaplas

If Not Serviceable.

Replace With:

LE8T-H

Visual Change:

Yes

Baffle Modification:

No

Exact Acoustic Replacement: No.

Slightly different. Replace both units

in a stereo pair.

FULL RANGE DRIVER (Cont'd)

Additional Parts Currently Available*:

Mounting Gasket: 21769

Trim Gasket: 21812

SYSTEM NOTES:

Early Models Rated At 16 Ohm

SYSTEM SPECIFICATIONS:

Nominal Impedance:

8 Ohm

Power Capacity:

20 Watts

Crossover Frequency:

N/A

Sensitivity:

Not Available

Enclosure Dim:

12-3/4" x 23-1/2" x 11-3/4" D

323mm x 597mm x 298mm

Shipping Weight:

42 lbs. - 19 kg.

Additional Parts Currently Available*:

^{*}Other parts may also be available. Check with JBL for details.