

Log In! Register to Shop Shopping Cart Checkout Shop New Category

SITE SEARCH



Home

Products

What's New?

Services

Tech Support

Training

Document Library

Mfr. Cross Reference


Distributor Inventory

Sales Contacts

Omron Worldwide

Omron Sites

> G8P-1A4P-DC12 Power PCB Relay



Download

- ⌘ Complies with UL508/UL873 Column A coil-to-contact s up to 300V
- ⌘ UL Class F coil insulation withstands higher ambient ter up to 105 degrees C
- ⌘ High switching capacity for appliance and HVAC applica
- ⌘ Wide range of coil ratings from 5 to 110 VDC
- ⌘ Choice of configurations to match most designs
- ⌘ High impulse withstand of 6kV
- ⌘ UL and CSA certified and VDE pending

● Stock Item ■ No

Part #	Stock Type	List Price [USD]	Add to Cart
G8P-1A4P-DC12	<span style="color: green;">●</span>	log on first	<span style="background-color: orange; color: white; padding: 2px;">ADD TO C</span>
See ALL Parts in this Product Family			

> Product Attributes

Relay Type	Electro-mechanical
Dielectric Strength	2500 VAC
Contact Configuration	SPST-NO
Output / Contact Rating	30 A
Input Power / Current	77 mA
Coil Voltage	12 VDC
Termination Configuration	PCB
Construction	Sealed

> Dimensions

- ⌘ Height 28.3000 mm
- ⌘ Length 32.1000 mm
- ⌘ Width 27.5000 mm

> Ordering Notes

**> Approvals**

- ✎ VDE Approval
- ✎ UL Approval
- ✎ CSA Approval

**> Environmental Ratings**

- ✎ No Environmental Ratings

**> Accessories**

- ✎ No Accessories defined